

SOFAR 10k~15kTL-G2

10000 / 12000 / 15000



Three-Phase

Dual-MPPT



Fuse free design



Max. efficiency up to 98.3%



Built-in DRM port and logic



Outdoor IP65 protection level



I-V curve scanning function



Smart control and flexible configuration

Datasheet

SOFAR I1000TL-G2

SOFAR I2000TL-G2

SOFAR I5000TL-G2

Input (DC)

Max. PV input power	18000Wp	18000Wp	19950Wp
Max DC power for single MPPT	11000W/7500W	11000W/7500W	11000W/7500W
Number of MPP trackers		2	
Number for DC inputs		3	
Max. input voltage		1000V	
Start-up voltage		200V	
Rated input voltage		600V	
MPPT operating voltage range		160V-960V	
Full power MPPT voltage range		300V-840V	
Max. input MPPT current		21A/11A	
Maximum DC input short circuit current per MPPT		30A/15A	

Output (AC)

Rated power	10000W	12000W	15000W
Max. AC power	11000VA	13200VA	16500VA
Max. Output current	3*16.5A	3*20A	3*24A
Nominal grid voltage		3/N/PE, 220/380Vac, 230/400Vac, 240/415Vac	
Grid voltage range		310Vac-480Vac (According to local standard)	
Nominal frequency		50/60Hz	
Grid Frequency range		45Hz-55Hz/54Hz-66Hz (According to local standard)	
Active power adjustable range		0~100%	
THDi		<3%	
Power factor		>0.99 (adjustable +/-0.8)	

Performance

Max efficiency	98.3%
European weighted efficiency	98.0%
Self-consumption at night	<1W
MPPT efficiency	>99.9%

Protection

DC reverse polarity protection	Yes
DC switch	Yes
ARPC	Anti reverse power controller (optional)
Safety protection	Anti islanding, RCMU, Ground fault monitoring

Communication

Power management unit	According to certification and request
Standard communication mode	RS485, Wifi/Ethernet/GPRS (optional), SD card
Operation data storage	25 years

General Data

Ambient temperature range	-25°C~+60°C		
Topology	Transformer-less		
Degree of protection	IP65		
Allowable relative humidity range	0~100%		
Max. Operating altitude	2000m		
Noise	<45dB		
Weight	23.5kg	23.5kg	25kg
Cooling	Fan		
Dimension	539*452*202mm		
Display	LCD display		
Warranty	5 years/ 7 years/ 10 years		

Standard

EMC	EN 61000-6-1, EN 61000-6-3
Safety standards	IEC62109-1/2, IEC62116, IEC61727, IEC-61683, IEC60068(1,2,14,30)
Grid standards	AS/NZS 4777, VDE-AR-N 4105, CEI 0-21, EN50549, V 0126-1-1, NB/T32004

SOFAR 20k~33kTL-G2

20000/ 25000/ 30000/ 33000



Three-Phase Dual-MPPT

- 4"** Super large 4-inch LCD
- 1100V** 1100V voltage level design
- DRM** Built-in DRM port and logic
- 98.6%** Max. efficiency up to 98.6%
- I-V** I-V curve scanning function
- SPD** Built-in SPD, over / under pressure, over current, over temperature, island and other multiple protections

Datasheet

	SOFAR 20000TL-G2	SOFAR 25000TL-G2	SOFAR 30000TL-G2	SOFAR 33000TL-G2
Input (DC)				
Recommended Max. PV input power	26600Wp	33250Wp	39900Wp	43890Wp
Max DC power for single MPPT	13000W	16000W	18000W	20000W
Number of MPP trackers	2			
Number for DC inputs	2 for each MPPT	3 for each MPPT	3 for each MPPT	3 for each MPPT
Max. input voltage	1100V			
Start-up voltage	250V			
Rated input voltage	620V			
MPPT operating voltage range	230V-960V			
Full power MPPT voltage range	480V-850V	460V-850V	520V-850V	580V-850V
Max. input MPPT current	24A/24A	28A/28A	30A/30A	30A/30A
Maximum DC input short circuit current per MPPT	30A	35A	37.5A	37.5A
Output (AC)				
Rated power	20000W	25000W	30000W	33000W
Max. AC power	22000VA	27500VA	33000VA	36300VA
Max. Output current	32A	40A	48A	53A
Nominal grid voltage	3/N/PE, 220/380Vac, 230/400Vac, 240/415Vac			
Grid voltage range	310Vac-480Vac (According to local standard)			
Nominal frequency	50/60Hz			
Grid Frequency range	45Hz-55Hz/54Hz-66Hz (According to local standard)			
Active power adjustable range	0~100%			
THDi	<3%			
Power factor	>0.99 (adjustable +/-0.8)			
Performance				
Max efficiency	98.2%	98.4%	98.4%	98.6%
European weighted efficiency	98.0%	98.2%	98.2%	98.2%
Self-consumption at night	< 1W			
MPPT efficiency	>99.9%			
Protection				
DC reverse polarity protection	Yes			
DC switch	Yes			
Protection class/ overvoltage category	I/III			
Safety protection	Anti islanding, RCMU, Ground fault monitoring			
ARPC	Anti reverse power controller (optional)			
Communication				
Power management unit	According to certification and request			
Standard communication mode	RS485, Wifi/Ethernet/GPRS(optional), SD card			
Operation data storage	25 years			
General Data				
Ambient temperature range	-25°C ~ +60°C			
Topology	Transformer-less			
Degree of protection	IP65			
Allowable relative humidity range	0~100%			
Max. operating altitude	2000m			
Noise	<30dB	<45dB	<45dB	<45dB
Weight	37kg			
Cooling	Natural	Fan	Fan	Fan
Dimension	666*512*254mm			
Display	LCD display			
Warranty	5 years/ 7 years/ 10 years			
Standard				
EMC	EN 61000-6-2, EN 61000-6-3, EN 61000-3-11, EN 61000-3-12			
Safety standards	IEC62109-1/2, IEC62116, IEC61727, IEC-61683, IEC60068(1, 2, 14, 30), IEC60255			
Grid standards	AS/NZS 4417, VDE V 0124-100, V 0126-1-1, VDE-AR-N 4105, CEI 0-21/CEI 0-16, EN 50549, G59, P.O. 12.3, RD 1699, UTE C15-712-1, EN 50530, NB/T32004			