

Trinahome S Series (NCA Type Battery)

Trina Energy Storage Solutions for New Residential Installations



PV & Battery Hybrid System

Rated Power: 3.7 kW
(Single-phase)



Capacity: 3 kWh - 12 kWh
(Expandable in steps of 3 kWh)

Warranty: 10 years Battery Performance
(Expected Lifetime 20 years)



Plug & Play



Backup Possible



Visualisation



Self-Consumption



Modular Customised



Easy Installation



Reliable Performance



Proven Safety

Germany:
Trina Energie Storage Vertrieb und Service GmbH
Tel: +49 (0) 69 75844 361
Email: eu.sales@trinabess.com
Add: Otto-Schott-Str. 4, 60438, Frankfurt, Germany





China:
Trina Energy Storage Solutions (Jiangsu) Co., Ltd.
Tel: +86 519 8517 6686
Email: trinabess@trinagroup.com
Add: No. 2 Tianhe Road, Trina PV Park, New District, Changzhou, Jiangsu

Oceania:
Trina Energy Storage Solutions (Australia) Pty. Ltd.
Email: australia.sales@trinabess.com
Add: 44.05, Level 44, 1 Farrer Place Sydney, NSW, 2000

Japan:
Trina Energy Storage Japan Co., Ltd.
Tel: +81 (0) 3 6432 0581
Email: jp.sales@trinabess.com
Add: 21F World Trade Center Building, 4-1, 2-chome, Hamamatsu-cho, Minato-ku, Tokyo 105-6121 Japan

Hybrid Inverter		TB3700SH
PV Input		
Max. PV Input Power / Max. PV Array Size	3700 W / 4800 W	
Max. PV Voltage	550 V	
MPP Voltage Range	125 - 530 V	
MPP Tracker	2	
Max. Input Current	2 * 12 A	
Max. Short-circuit Current, Module Array	2 * 15 A	
Start PV Voltage	125 V	
Battery Input (DC)		
Max. Charging / Discharging Power*	2400 W / 2400 W	
Max. Charging / Discharging Current	50 A / 50 A	
Operation Voltage Range	40 - 60 V	
Battery Full Power Voltage Range	48 - 60 V	
AC Output		
Max. Output Power	3600 W	
Rated Output Voltage	230 Vac	
Rated Output Frequency	50 Hz	
AC Nominal Current	16 A	
Back-up Function Possible (Integrated)		
Max. Auto-switching Time	< 5 Seconds	
AC Rated Frequency	50 Hz	
Max. Backup Supply Power	2 kVA	
Other Parameters		
Max. efficiency (PV - battery - grid)	≥ 80 %	
Max. efficiency (PV - grid)	≥ 95 %	
IP Protection Class	IP 20	
Noise	< 55 dB	
Dimension (W x H x D)	660 x 520 x 170 mm	
Weight	< 35 kg	
Cooling	Forced Air Cooling	
Certificate	VDE 4105, G 83, AS 4777, IEC 62109	

Battery Packs

Nominal Voltage	51.8 V			
Usable Battery Capacity	1 * 3 kWh	2 * 3 kWh	3 * 3 kWh	4 * 3 kWh
Module Appearance and Dimension (W x H x D) / Weight	 790 x 220 x 190 mm < 35 kg	 790 x 440 x 190 mm < 70 kg	 790 x 660 x 190 mm < 105 kg	 790 x 880 x 190 mm < 140 kg
Other Parameters				
Battery Cell	NCA			
DOD	100 %			
Cycle Life	> 8000			
Communication	CAN2.0			
Certificate	UN 38.3, CE			
IP Protection Class	IP 21			

System

Humidity	0 ~ 95 %
Operating Temperature Range	-10 ~ 45 °C (-10 ~ 0 °C with derating)
Warranty	5 years product, 10 years battery performance

* The actual Max. charging / discharging will be depending on different output voltage of connected battery bank.
CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

