







Single Phase String Inverter

SUN- 3.6 / 4 / 4.6 / 5 / 6 K-G04-AU



-  2 MPP trackers, Max. efficiency up to 97.5%
-  Zero export application, VSG application
-  String intelligent monitoring (optional)
-  Wide output voltage range
-  Anti-PID function (Optional)
-  80 Low start-up voltage of 80V

Deye

Stock Code: 605117.SH

Model	SUN-3.6K-G04-AU	SUN-4K-G04-AU	SUN-4.6K-G04-AU	SUN-5K-G04-AU	SUN-6K-G04-AU
Input Side					
Max. DC Input Power (kW)	4.7	5.2	5.98	6.5	7.8
Max. DC Input Voltage (V)	550				
Min. DC Input Voltage (V)	70				
Start-up DC Input Voltage (V)	80				
MPPT Operating Range (V)	70~500				
Max. DC Input Current (A)	13+13				
Max. Short Circuit Current (A)	19.5+19.5				
Number of MPPT / Strings per MPPT	2/1				
Output Side					
Rated Output Power (VA)	3.6	4	4.6	5	6
Max. Active Power (kW)	3.6	4	4.6	5	6
Nominal Output Voltage / Range (V)	L/N/PE 230V/ 195.5V-253V				
Rated Grid Frequency (Hz)	50Hz/45Hz-55Hz				
Operating Phase	Single phase				
Rated AC Grid Output Current (A)	15.7	17.4	20	21.7	26.1
Max. AC Output Current (A)	15.7	17.4	20	21.7	26.1
Output Power Factor	0.8 leading to 0.8 lagging				
Grid Current THD	<3%				
DC Injection Current (mA)	<0.5%				
Grid Frequency Range	47~52 or 57~62 (Optional)				
Efficiency					
Max. Efficiency	97.3%	97.5%	97.5%	97.5%	97.5%
Euro Efficiency	97.1%	97.3%	97.3%	97.3%	97.3%
MPPT Efficiency	>99%				
Protection					
DC Reverse-Polarity Protection	Yes				
AC Short Circuit Protection	Yes				
AC Output Overcurrent Protection	Yes				
Output Overvoltage Protection	Yes				
Insulation Resistance Protection	Yes				
Ground Fault Monitoring	Yes				
Anti-islanding Protection	Yes				
Temperature Protection	Yes				
Integrated DC Switch	Yes				
Remote software upload	Yes				
Remote change of operating parameters	Yes				
Surge protection	DC Type II / AC Type III				
General Data					
Size (mm)	330W×323H×190D				
Weight (kg)	7.5				
Topology	Transformerless				
Internal Consumption	<1W (Night)				
Running Temperature	-25~65°C, >45°C derating				
Ingress Protection	IP65				
Noise Emission (Typical)	<25 dB				
Cooling Concept	Natural cooling				
Max. Operating Altitude Without Derating	2000m				
Warranty	5 years				
Grid Connection Standard	AS/NZS 4777.2				
Operating Surroundings Humidity	0-100%				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				
Features					
DC Connection	VP-D4				
AC Connection	IP65 rated plug				
Display	LCD1602				
Interface	RS485/RS232/Wifi/LAN				