

# Hybrid Inverter

SUN- 3 / 3.6 / 5 / 6 K-SG04LP1-AU



Colorful touch LCD, IP65 protection degree



AC couple to retrofit existing solar system

16

Max. 16pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel

135

Max. charging/discharging current of 135A

6

6 time periods for battery charging/discharging



Support storing energy from diesel generator

**Deye**

Stock Code: 605117.SH

Model	SUN-3K -SG04LP1-24-AU	SUN-3K -SG04LP1-AU	SUN-3.6K -SG04LP1-AU	SUN-5K -SG04LP1-AU	SUN-6K -SG04LP1-AU
<b>Battery Input Data</b>					
Battery Type	Lead-acid or Li-Ion				
Battery Voltage Range (V)	20-30	40-60	40-60	40-60	40-60
Max. Charging Current (A)	140	70	90	120	135
Max. Discharging Current (A)	140	70	90	120	135
External Temperature Sensor	Yes				
Charging Curve	3 Stages / Equalization				
Charging Strategy for Li-Ion Battery	Self-adaption to BMS				
<b>PV String Input Data</b>					
Max. PV Input Power (W)	4500	4500	5400	7500	9000
Rated PV Input Voltage (V)	370 (125~500)				
Start-up Voltage (V)	125				
MPPT Voltage Range (V)	150~425				
Full Load PV Voltage Range (V)	300~425				
PV Input Current (A)	13			13+13	
Max. PV I <sub>sc</sub> (A)	19.5			19.5+19.5	
Number of MPPT / Strings per MPPT	1/1			2/1+1	
<b>AC Output Data</b>					
Rated AC Output and UPS Power (VA)	3000		3600	5000	6000
Max. AC Output Power (W)	3000		3600	5000	6000
AC Output Rated Current (A)	13		15.7	21.7	26.1
Max. AC Output Current (A)	13		15.7	21.7	26.1
Max. Continuous AC Passthrough (A)			35		40
Peak Power (off grid)	2 time of rated power, 10 S				
Power Factor	0.8 leading to 0.8 lagging				
Output Frequency and Voltage	230V/240V0.85Un-1.1Un				
Grid Connection Form	L+N+PE				
Total Harmonics Current Distortion (THDi)	< 3% ( of nominal power )				
DC current injection	<0.5% I <sub>n</sub>				
<b>Efficiency</b>					
Max. Efficiency	97.60%				
Euro Efficiency	96.50%				
MPPT Efficiency	99.90%				
<b>Protection</b>					
Integrated	Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Surge protection				
Over Voltage Category	DC Type II/AC Type III				
<b>Certifications and Standards</b>					
Grid Regulation	AS/NZS 4777.2				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				
<b>General Data</b>					
Operating Temperature Range ( )	-40 to +60 , >45 derating				
Cooling	Free cooling				Smart cooling
Noise (dB)	< 30 dB				
Communication Interface	RS485/RS232				
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)				
Weight (kg)	17			17	
Size (mm)	333W x 433H x 229D ( Excluding connectors and brackets)				
Protection Degree	IP65				
Installation Style	Wall-mounted				
Warranty	10 Years				