

RESIDENTIAL ESS SOLUTION

DEYE SPRING AI SERIES



All-in-One

- Integrated hybrid inverter
- And LFP battery



Smarter

- Peak-shaving, smart load
- AC coupling, etc.



Scalable

- Flat and stackable design
- Capacity of 5kWh~30kWh



Swift Security

- Fast switching time of 4ms
- Ensuring energy security




Flexible

- No wiring and extra fixing screws
- Quick and easy installation



Convenient

- Comfortable and easy control
- Via App, PC or Touch-Display



IP65

Rated for indoor and outdoor use

10 years


Warranty for long-term peace of mind

Model	AI-W5.1-3.6P1-AU-B	AI-W5.1-5P1-AU-B	AI-W5.1-6P1-AU-B	AI-W5.1-7P1-AU-B	AI-W5.1-7.6P1-AU-B	AI-W5.1-8P1-AU-B	AI-W5.1-10P1-AU-B
Battery Input Data							
Battery Type	Lithium-ion						
Battery Voltage	40-60						
Max. Charging Current(A)	90	120	135	175	190	190	210
Max. Discharging Current(A)	90	120	135	175	190	190	210
Charging Strategy for Li-Ion Battery	Self-adaption to BMS						
Number of Battery Input	1						
PV String Input Data							
Max. PV access power(W)	7200	10000	12000	14000	15200	16000	20000
Max. PV Input Power(W)	5760	8000	9600	11200	12160	12800	16000
Max. PV Input Voltage(V)	500						
Start-up Voltage(V)	125						
PV Input Voltage Range(V)	125-500						
MPPT Voltage Range(V)	150-425						
Full Load MPPT Voltage Range(V)	300-425		200-425			250-425	
Rated PV Input Voltage(V)	370						
Max. Operating PV Input Current(A)	13+13			26+26			
Max. Input Short-Circuit Current(A)	19.5+19.5			39+39			
No.of MPPT Trackers/No.of String MPPT Tracker	2/1+1			2/2+2			
Max. Inverter Backfeed Current to The Array	0						
AC Input/Output Data							
Rated AC Input/Output Active Power(W)	3600	5000	6000	7000	7600	8000	9999
Max. AC Input/Output Apparent Power(VA)	3600	5000	6000	7000	7600	8000	9999
Peak Power (off-grid)(W)	2 times of rated power, 10s						
Rated AC Input/Output Current(A)	15.7	21.8	26.1	30.5	33	34.8	43.5
Max. AC Input/Output Current(A)	15.7	21.8	26.1	30.5	33	34.8	43.5
Max. Continuous AC Passthrough (grid to load)(A)	35		40	50			
Max. Output Fault Current(A)	31.4	43.4	52.2	61	69.6	66	100
Max. Output Overcurrent Protection(A)	80			140			
Rated Input/Output Voltage/Range(V)	230V/240V 0.85Un-1.1Un						
Grid Connection Form	L+N+PE						
Rated Input/Output Grid Frequency/Range	50Hz/45Hz-55Hz						
Power Factor Adjustment Range	0.8 leading-0.8 lagging						
Total Current Harmonic Distortion THDI	<3% (of nominal power)						
DC Injection Current	<0.5%In						
Efficiency							
Max. Efficiency	97.60%						
Euro Efficiency	96.50%						
MPPT Efficiency	>99%						
Equipment Protection							
DC Polarity Reverse Connection Protection	Yes						
AC Output Overcurrent Protection	Yes						
AC Output Overvoltage Protection	Yes						
AC Output Short Circuit Protection	Yes						
Thermal Protection	Yes						
Arc fault circuit interrupter (AFCI)	Optional						
Power Network Monitoring	Yes						
Island Protection Monitoring	Yes						
Earth Fault Detection	Yes						
DC Input Switch	Yes						
Overvoltage Load Drop Protection	Yes						
Residual Current (RCD) Detection	Yes						
Anti-islanding Protection	Yes(Active Frequency Shift)						
Surge Protection Level	TYPE II(DC), TYPE II(AC)						
Interface							
Display	LCD+LED						
Communication Interface	RS232, RS485, CAN						
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN (optional)						
PV Connection	VP-D4						
General Data							
Operating Temperature Range	-40 to +60°C, >45°C Derating						
Permissible Ambient Humidity	0-100%						
Permissible Altitude	2000m						
Noise	<30 dB(A)						
Ingress Protection(IP) Rating	IP 65						
Inverter Topology	Non-Isolated						
Over Voltage Category	OVC II(DC), OVC III(AC)						
Protection Level	Class I						
Cabinet size(W*H*D) [mm]	720W×399.2H×256D (Excluding connectors and brackets)						
Weight(kg)	31.6						
Warranty	10 Years						
Type of Cooling	Intelligent Air Cooling						
Grid Regulation	AS/NZS 4777.2						
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2						


Model	AI-W5.1-5P3-AU-B	AI-W5.1-6P3-AU-B	AI-W5.1-8P3-AU-B	AI-W5.1-10P3-AU-B	AI-W5.1-12P3-AU-B
Battery Input Data					
Battery Type	Lithium-ion				
Battery Voltage	40-60				
Max. Charging Current(A)	120	150	190	210	240
Max. Discharging Current(A)	120	150	190	210	240
Charging Strategy for Li-Ion Battery	Self-adaption to BMS				
Number of Battery Input	1				
PV String Input Data					
Max. PV access power(W)	10000	12000	16000	20000	24000
Max. PV Input Power(W)	7500	9000	12000	15000	18000
Max. PV Input Voltage(V)	800				
Start-up Voltage(V)	160				
PV Input Voltage Range(V)	160-800				
MPPT Voltage Range(V)	200-650				
Full Load MPPT Voltage Range(V)	350-650				
Rated PV Input Voltage(V)	550				
Max. Operating PV Input Current(A)	13+13			26+13	
Max. Input Short-Circuit Current(A)	19.5+19.5			39+19.5	
No.of MPPT Trackers/No.of String MPPT Tracker	2/1+1			2/2+1	
Max. Inverter Backfeed Current to The Array	0				
AC Input/Output Data					
Rated AC Input/Output Active Power(W)	5000	6000	8000	10000	12000
Max. AC Input/Output Apparent Power(VA)	5000	6000	8000	10000	12000
Peak Power (off-grid)(W)	2 times of rated power, 10s				
Rated AC Input/Output Current(A)	7.2	8.7	11.6	14.5	17.4
Max. AC Input/Output Current(A)	7.2	8.7	11.6	14.5	17.4
Max. Continuous AC Passthrough (grid to load)(A)	45				
Max. Output Fault Current(A)	14.4	17.4	23.2	29	34.8
Max. Output Overcurrent Protection(A)	70				
Rated Input/Output Voltage/Range(V)	230V/400V 240V/415V 0.85Un-1.1Un				
Grid Connection Form	3L+N+PE				
Rated Input/Output Grid Frequency/Range	50Hz/45Hz-55Hz				
Power Factor Adjustment Range	0.8 leading-0.8 lagging				
Total Current Harmonic Distortion THDI	<3% (of nominal power)				
DC Injection Current	<0.5%In				
Efficiency					
Max. Efficiency	97.6%				
Euro Efficiency	97.0%				
MPPT Efficiency	>99%				
Equipment Protection					
DC Polarity Reverse Connection Protection	Yes				
AC Output Overcurrent Protection	Yes				
AC Output Overvoltage Protection	Yes				
AC Output Short Circuit Protection	Yes				
Thermal Protection	Yes				
Arc fault circuit interrupter (AFCI)	Optional				
Power Network Monitoring	Yes				
Island Protection Monitoring	Yes				
Earth Fault Detection	Yes				
DC Input Switch	Yes				
Overvoltage Load Drop Protection	Yes				
Residual Current (RCD) Detection	Yes				
Anti-islanding Protection	Yes(Active Frequency Shift)				
Surge Protection Level	TYPE II(DC), TYPE II(AC)				
Interface					
Display	LCD+LED				
Communication Interface	RS232, RS485, CAN				
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN (optional)				
PV Connection	VP-D4				
General Data					
Operating Temperature Range	-40 to +60°C, >45°C Derating				
Permissible Ambient Humidity	0-100%				
Permissible Altitude	2000m				
Noise	≤ 55 dB				
Ingress Protection(IP) Rating	IP 65				
Inverter Topology	Non-Isolated				
Over Voltage Category	OVC II(DC), OVC III(AC)				
Protection Level	Class I				
Cabinet size(W*H*D) [mm]	720W×440H×254D (Excluding connectors and brackets)				
Weight(kg)	39.75				
Warranty	10 Years				
Type of Cooling	Intelligent Air Cooling				
Grid Regulation	AS/NZS 4777.2				
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				



Model	Accessories Parts Description	Remark
AI-W5.1-B Module (individual package)	5.12kWh Battery Module (Standard Configuration)	Stacked battery modules, each 5.12kWh, a single inverter can be stacked and installed 1 ~ 6 (battery capacity 5~30kWh) , the maximum expansion of 36 modules to 184kWh.
AI-W5.1-PDU3-B+Base (individual package) (Optional 1)	Power Distribute Unit III (Included)	Battery power and communication quickly interface connect with Inverter and LED display system status, only support 2 ~ 6 modules expansion, capacity 10 ~ 30kWh.
	AI-W5.1-Base (Included)	The bottom support seat



Model : AI-W5.1-B (Battery Module)
 Details : 5.12kWh, 720 × 255 × 300 (W × D × H, mm) , 55kg



Model : AI-W5.1-PDU3-B
 Details : 720 × 255 × 228 (W × D × H, mm) , 15kg
 Built-in Circuit Breaker: 250A 2P, 1000Vdc



Model : AI-W5.1-Base (Battery Base)
 Details : 720 × 255 × 68 (W × D × H, mm) , 6.5kg



Model : AI-W5.1-BCable1500
 Details : Pair of 2/0AWG DC power cable and RJ45 communication cable for external battery expansion of AI-W5.1-PDU2, power cable one end has a waterproof terminal, communication cable both ends have waterproof terminals. The cable length can be customized based on customer requirements, default length is 1500mm.



POWERING YOUR LIFE

