

STAR Pro SERIES N-TOPCon 108-cell MODULE

EG-440NT54-HLV

440W

OSW Specified

KEY FEATURES



SMBB cell design
Super multi Busbar cells brings lower resistance and increased Busbar reflectance ensures higher power output



Low degradation
Adopt N-Type TOPCon cell technology, lower degradation and better temperature co-efficiency, greatly increased on generation performance



High Reliability
Strict in-house testing in PV Lab which is CNAS approved & TUV /VDE certified




Excellent Low-light Performance
Advanced solar cell and glass surface texturing technology allows for excellent performance in low-light environments



PID Resistant
Excellent PID resistance performance optimized by unique structural design

LINEAR PERFORMANCE WARRANTY


25 25 Year Product Warranty **30** 30 Year Linear Power Warranty




As a BloombergNEF Tier 1 and global leading manufacturer since 1998, EGING PV is committed to supplying reliable and durable PV products to customers to create together a greener planet.

EG-440NT54-HLV

Engineering Drawings



I-V Curves



Packing Configuration

Pieces per pallet	36
Size of packing (mm)	1750*1135*1255
Weight of packing (kg)	772
Pieces per container	936
Size of container	40'HC

Electrical Characteristics

Power level	440
Pmax (W)	440
Vmp (V)	32.24
Imp (A)	13.65
Voc (V)	38.80
Isc (A)	14.40
Module efficiency (%)	22.53
Maximum system voltage (V)	1500
Fuse Rating (A)	25
Power tolerance (%)	Pmax: ±3% Binning: 5W Voc: ±5% Isc: ±5%
Temperature coefficient Pmax (%/°C)	-0.30
Temperature coefficient Isc (%/°C)	0.046
Temperature coefficient Voc (%/°C)	-0.25

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

Working Characteristics

Power level	440
Pmax (W)	331
Vmp (V)	29.88
Imp (A)	11.08
Voc (V)	36.81
Isc (A)	11.69
Power tolerance (%)	Pmax: ±3%
NOCT (°C)	44±2

NOCT: Conditions: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Mechanical Characteristics

Number of cells	108pcs
Size of cell (mm)	182*91
Type of cell	N-type Mono
Thickness of glass (mm)	3.2
Type of frame	Anodized aluminum alloy
Junction box	IP68
Size of module (mm)	1722*1134*30
Weight (kg)	20.2
Cables/connectors	62930 IEC 131, 1*4mm²/E1-X, QC4.10-cd, Z4S, RHC2xyzu
Length of Cabel	Portrait: +1000mm/-1000mm

Maximum Ratings

Operating Temperature(°C)	-40~85
Operating humidity(°C)	5~85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s

Revised in August 2023 1st Edition

CAUTION: All rights and explain reserved by EGING PV.
Specifications included in this datasheet are subject to change without notice.
The specific content of the product warranty refers to EGING's latest warranty.



Tel: 86-519-82585880
Zip: 213213
Add: No.18, Jinwu Road, Jintan Dist,
Changzhou City, Jiangsu Province.
Email: marketing@egingpv.com
Web: www.egingpv.com